



WITH MECHANICAL SPINDLE CLUTCH AND 3 AXIS READ OUT, SEMI NORTON GEAR BOX. EQUIPPED WITH A JOYSTICK FOR THE INSERTION OF RAPID...



FERVIplus



Centers height	280 mm
Max swing over the bed	560 mm
Max swing over the cross slide	360 mm
Max swing over the gap	770 mm
Tool height	32 mm
Distance between centers	1500 mm
Spindle bore	105 mm
Spindle nose Camlock	Camlock D1-8
Spindle speed	(12) 36 - 1600 rpm
Longitudinal feeds	0,063 - 2,52 mm/giro
Cross feeds	0,027 - 1,07 mm/rev
Metric threads	(22) 1 - 14 mm
Inch threads	(26) 2 - 28 TPI
Tailstock taper MT	5
Motor	400V 50/60 Hz 7,5 kW
Cooling pump	400V 50/60 Hz 90 W
Dimensions	3000 x 1400 x 1500 mm
Net weight	3210 Kg
Gross weight	3555,00 kg
EAN Code	8012667402167
Packaging dimensions	3000 x 1400 x 1500h mm

Included

3 reversible jaw self centering chuck Ø 320 mm
4 independent jaw chuck Ø 400 mm
Face plate Ø 600 mm
Follow rest
Steady rest
Live center MT 5
Thread dial
Leadscrew hood
Tool post guard
Chuck safeguard
Full length splash guard
Italy style quick change tool post type C
Working LED lamp
Cooling system
Electromechanical foot brake
Tailstock carriage a quick locking
Wagon gears in oil bath
Adjustable leveling feet