

WITH SEMI NORTON GEAR BOX. TURNING BAR WITH ADJUSTABLE CLUTCH.



FERVIplus



Centers height	160 mm
Max swing over the bed	320 mm
Max swing over the cross slide	180 mm
Tool height	16 mm
Distance between centers	1000 mm
Spindle bore taper MT	5
Spindle bore	38 mm
Spindle nose Camlock	Camlock D1-4
Spindle speed	(18) 75-1800 rpm
Longitudinal feeds	(40) 0,053 - 1,291 mm/rev
Cross feeds	(40) 0,011 - 0,275 mm/rev
Metric threads	(32) 0,4 - 7 mm
Inch threads	(36) 4 - 60 TPI
Tailstock taper MT	3
Motor	400 V 50/60 Hz 1.3 kW
Dimensions	1850 x 700 x 1550 mm
Net weight	550 Kg
Gross weight	540,00 kg
EAN Code	8012667406325
Packaging dimensions	1860x760x1600 h mm

Included

3+3 jaw self centering chuck Ø 160 mm
4 Reversible independent jaws chuck Ø 200 mm
Face plate Ø 250 mm
Follow rest
Steady rest
Reduction sleeve MT 5/3
Dead center MT 3
Dead center MT 5
Live center MT 3
Foot brake
Thread dial
Leadscrew protection
Turret protection
Chuck safeguard
Full length splash guard
TOAE quick change tool post
Working lamp LED
Quick locking tailstock carriage
Cooling system
Clutch on turning bar
Wagon gears in oil bath