


UTILIZZATE PRINCIPALMENTE NEI TORNİ CON Lâ€™OBIETTIVO DI
STABILIZZARE I PEZZI LUNGHİ E SOTTILI, PIÙ SOGGETTI ALLA
FLESSIONE O..



€309,00



Cono morse

A	4
B	L2 61,5 mm - D2-D3 28 mm - $\hat{I} \pm 60^\circ$ mm
C	L2 55,5 mm - D2-D3 28 mm - $\hat{I} \pm 75^\circ$ mm
D	L2 51,5 mm - D2-D3 28 mm - $\hat{I} \pm 90^\circ$ mm
E	L2 69 mm - D2-D3 26 mm - $\hat{I} \pm 60^\circ$ mm
F	L2 61,5 mm - D2-D3 50 mm / 28 mm - $\hat{I} \pm 60^\circ$ mm
G	L2 55 mm - D2-D3 40 mm / 35 mm - $\hat{I} \pm 60^\circ$ mm
G	L2 60 mm - D2-D3 55 mm / 48 mm - $\hat{I} \pm 60^\circ$ mm

Max rpm

5000 g/min

Portata max

240 kg

Peso lordo

3,88 kg

Dimensioni imballo

380x225x110 h mm

Codice EAN

8012667011178



Valigetta



Temprato



9 Pcs



Acciaio



Rettificato